



### **HIGHLIGHTS**

- Connect wirelessly to WioT Gateway and transmits motion detection status information instantly
- · Automatically connect to the associated WioT gateway
- · Supports multiple zones
- · Last for 3+ Years on a single battery
- · No drilling or holes required
- · Waterproof, ruggedized design

#### **ADDED VALUE**

### **Emergency & Safety Monitoring**

- · Monitor motion in closed or targeted area(s)
- Monitor motion inside a parked vehicle
- $\boldsymbol{\cdot}$  Wake-up the system and send alerts when motion is detected

### For D.O.T. Compliance

· Monitor motion in parked & amp; empty vehicle

# Wiot Motion Sensor

Model: WS-MTD-100

The WS-MTD-100 motion sensor is a wireless sensor that detects any motion using advanced infrared technology. This motion sensor is fully automated and seamlessly connects with the WioT Gateway system.

Multiple WS-MTD-100 motion sensors can be deployed in the same environment at multiple access points in order to increase safety. The WS- MTD -100 is easy to install on any surface.

### **TECHNICAL SPECIFICATION**

| Sensors Mechanism   | Infrared   |
|---------------------|--|
| Normal State        | Can be determined by the installation or the configuration     |
| Alarm State         | Can be determined by the installation or the configuration     |
| Other Alarms        | Use logic to combine with additional sensor(s)                 |
| Use Case            | Inside a closed area to detect movement at the specific timing |
| Compatibility       | Integrated with all WioT Series                                |
| Update Frequency    | Real-time  |
| Trigger Sensitivity | Up to 5 meters (1 m/s motion)                                  |
| Data Transmission   | Wireless transmission via WioT<br>Gateway                      |
| Accuracy            | 100%   |



## PRODUCT SPECIFICATION

| Material              | Polycarbonate, PMMA  |
|-----------------------|--|
| Dimensions            | 8.0 x 4.0 x 2.0 cm   |
| Weight                | 69g  |
| Operating Temperature | -40 C° to 70 C°  |
| Operating Humidity    | Max. 95 %  |
| Battery               | 3.6 V, 3+ years battery life<br>Replaceable AA battery     |
| Wireless Frequency    | 433 MHz low-power data protocol                            |
| Range                 | 10-30 m (line of site), is depend on the physical obstacle |
| Ingress protection    | IP67 Rated, Waterproof and dustproof                       |
| Mounting Material     | 3M sticker and (optional) screws                           |

IN NORTH AMERICA +1 (289) 409-9692

2233 Argentia Road Suite #302, East Tower Mississauga, Ontario L5N 6A6 Canada IN MENA +1 (289) 409-9692

(Middle East & North Africa)
Post Production Media Building
Suite #504A, Ministries Complex
P.O.Box 769433, Abu Dhabi, UAE

**SUPPORT** 

Bring Wiot to your Business contact@innoventintegrated.com

www.wiotbox.com